



PURELUBE PASSENGER CAR MOTOR OIL

PureLube Passenger Car Motor Oils are specially formulated with high-quality Group II base oils plus state-of-the-art performance additives and are engineered to meet the demands of gasoline, propane, and natural gas engines in passenger cars and light duty trucks requiring API SN rated oils, as well as older service levels SM and SL. SAE 5W-30, 5W-20 and 10W-30 grades are also Resource Conserving and meet ILSAC GF-5, as well as older service level GF-4. 5W-20 and 5W-30 are synthetic blend formulations.

TYPICAL PROPERTIES						
SAE	5W-20 Synthetic Blend	5W-30 Synthetic Blend	10W-30	10W-40	20W-50	30
API Service	SN	SN	SN	SN	SN	SN
ILSAC	GF-5	GF-5	GF-5	---	---	---
Kinematic Viscosity cST@40°C	49.7	63.2	69.5	103.3	149.0	86.3
cST@100°C	8.6	10.6	10.6	15.1	18.8	11.1
Viscosity Index	150	155	140	151	142	116
CCS Viscosity cP@-30°C	6100	6300	---	---	---	---
cP@-25°C	---	---	6300	6400	---	---
cP@-15°C	---	---	---	---	6600	---
Evaporative Loss, NOACK, wt%	<15	<15	<15	<15	<15	---
Specific Gravity 15.6°C (60°F)	0.861	0.860	0.866	0.866	0.876	0.875
Flash Point, °C	218	224	234	236	242	240
Pour Point, °C	-39	-39	-36	-36	-30	-24
Color (ASTM)	3.0	3.0	L 3.5	L 3.5	L 3.5	L 3.5
Sulfated Ash, wt%	0.92	0.92	0.92	0.92	0.92	0.92

Note: Values shown above are representative of current production and may vary within modest ranges.

Distributed By:
HALCO LUBRICANTS
1015 NORCROSS INDUSTRIAL COURT
NORCROSS, GA 30071
770-840-3480 MAIN 800-766-5665 TOLL FREE
www.halcolubricants.com